



PH. 706-507-3610

Fax 706-507-3611

Model FB 48/80

www.dynaweldtrailers.net

STANDARD FEATURES	PLUS 12% FEDERAL EXCISE TAX
Load Capacity _____	80,000 Equally Distributed / 60,000 in 10' Span Closed
Weight _____	15,950 # +/- 3%
Overall Length _____	48' to 80'
Width _____	8'6"
Extendable Deck _____	Locking Pin Air Operated with 5 Positions & Greaseable Rollers
Deck Length _____	37' Closed
Deck Height _____	60"
Gooseneck _____	11'
Fifth Wheel Height _____	49"
King Pin Swing Radius _____	84"
King Pin Setting _____	24"
Mainframe _____	T1 Fabricated w/ Positive Camber
Cross Members _____	4" I-Beams (12" - 14" - 12" on Centers)
Side Rails _____	6" Channel Iron
Stake Pockets _____	4" Deep on 24" Centers
Front and Rear Stake Pockets _____	6 Across Front, 3 Across Rear
Rub Band _____	1/4"x 2 1/2" Steel
Pipe Spools _____	Double on 8" Centers
Sliding Winch Track _____	Entire Length of Road Side
Winches _____	12 Total - with Straps, 2 Recessed in Front Deck
Landing Gear _____	Two Speed, 50,000 lbs. Capacity
Decking _____	1-1/8" Apitong
Suspension _____	Air Ride 50,000 lb. Capacity, 49" Spacing
Axles _____	25K lb. Capacity, 77.5" Track, Auto Slack Adjusters, Type 30/30 Brake Chambers, Outboard Drums, ABS
Brakes _____	16 1/2" x 7"
Parking Brakes _____	Type 30/30 Spring Brakes (2 Axles Only)
Tires _____	255/70R22.5 Low Profile Radials
Wheels _____	8.25 x 22.5 Steel Disc/Hub Piloted
Wiring _____	D.O.T. Sealed Wiring Harness, Sealed Lights Rubber Mounted
Lights _____	L.E.D.
Track System _____	Air & Elect. Lines in a Track System for Protection & Efficiency
Mud Flaps _____	Spray Guard and Anti-Sail
Paint _____	Black (Two Part Primer w/ Two Part Polyurethane Paint)

NOTE ALL SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE. WEIGHTS AND DIMENSIONS ARE APPROXIMATE

OPTIONAL EQUIPMENT

GOOSENECK

Revolver Greaseless Coupling System (Eliminates Need To Grease 5th Wheel) _____

Additional Recessed Winch & Strap _____

Non-DOT Removable HB 48" High - 12 Gauge Sheets - No Side Return - 4 Posts - Square Front - Includes Pockets _____

DOT Removable HB 48" High - 12 Gauge Sheets - 21" Side Return - 6 Posts-Square Front - Includes Pockets _____

DOT Permanent - 48" High - 10 Gauge Sheets - No Return - 4 Posts _____

DOT Aluminum Removable - 48" High - .160 Aluminum Sheet - 10" Side Return _____

DECK

Additional Length In Deck Area _____ Per ft. _____

Additional Width 9' includes 83.5" Track Axles (\$75 per State Delivery Charges) _____

10' includes 95.5" Track Axles (\$75 per State Delivery Charges) _____

Rub Band - 3/8" x 3" Heavy Duty _____

Heavy Duty Coil Package - (12" - 12" - 12") - Lateral Bracing _____

BOGIE

No Type 30/30 Spring Brakes _____

Aluminum Wheels (8) (Outside Polished) _____

Additional Axle - Spring Suspension _____

Additional Axle - Airride Suspension _____

Hutch Spring Suspension _____ Deduct _____

Air Ride Slider (60" Slide) _____

Widespread Air Ride (10' 2") 50,000 lb. Cap _____

MISCELLANEOUS

Additional Lights L.E.D. _____ Each _____

Recessed "D" Rings on Top of Deck _____ Pair _____

Chain Tie Downs - Recessed in Floor with Pipe Sleeve - Hi-Test Chain Approx. 10" Long _____ Pair _____

Hubodometer _____

Special Paint Color (Black is Standard) _____