Georgia Office 706-507-3610 **Fax 706-507-3611**
California Office 510-582-4849 **Fax 510-582-9917**

Model LB35-24PS

STANDARD FEATURES	PLUS 12% FEDERAL EXCISE TAX
Load Capacity	70,000 lbs. In 16’
Weight	16,700lbs.
Overall Length	47’ 8”
Width	8’6”
Deck Length	24’ Cambered Deck
Deck Height	24” Loaded
Gooseneck	Hydraulic Removable, Non-Ground Bearing Design, Two 8” Main Cylinders
Power Source	Set Up For Wet Line
Fifth Wheel Height	48”
King Pin Swing Radius	90”
King Pin Setting	18”
Mainframe	16” Fabricated With Positive Camber (Four I-Beam Design)
Siderails	16” Fabricated With Positive Camber (Four I-Beam Design)
Cross Members	8” I-Beam Located on 20” Centers
Front Deck Ramps	18” x 42” Paver Front Flip Ramps
Rear Bridge	16 Degree Slope from Deck to Rear Bridge
Boom Trough	Flat w/ Wood Center
Wheel Wells	Covered with Check Plate
Lashing Rings	8 Per Side (16 total)
Decking	Full 1-3/4”Apitong, Entire Deck Floored
Widening Brackets	Extends Trailer Width Two Feet In Deck
Suspension	Air Ride with Auto & Manual Controls, - 3½” Down + 5” Up
Axles	25,000 lbs. Capacity, 77.5” Track, Auto Slack Adjusters, Type 30/30 Brake Chambers, 16 ½”x 7” Brake Pads, Outboard Drums, ABS, 49” Axle Spacings
Parking Brakes	Type 30/30 Spring Brakes (2 Axles)
Tires	255/70R22.5 Low Profile Radials
Wheels	8.25x 22.5 Steel Disc/Hub Piloted
Tool Box	In Front and Rear of Deck
Wiring	D.O.T. Sealed Wiring Harness, Rubber Mounted LED Lights
Paint	Yellow/Black (Two Part Primer w/ Two Part Polyurethane Paint)

*****NOTE*** ALL SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE. WEIGHTS AND DIMENSIONS ARE APPROXIMATE**

OPTIONAL EQUIPMENT

GOOSENECK

Self Contained 13 H.P. Honda Power Unit-Lockable (With Quick Disconnects)
Revolver Greaseless Coupling System (Eliminates Need To Grease 5th Wheel
Steel Non-Load Bearing Gooseneck Fenders
Dual King Pin (90” & 110”)

DECK

Additional Length In Deck Area (max. 2’) call for additional length
Center Deck Open
Additional Width 9’ includes 83.5” Track Axles
10’ includes 95.5” Track Axles
Aluminum Center Ramp
18” Loaded Deck Height Design (12” Mainbeams and Siderails)
Drop Side Design - Lowers Side Decks 5”
Floor Clips (In Lieu of Screws)

BOGIE

No Type 30/30 Spring Brakes (2 Axles Only)
Air Lift One Axle
Single Point (2 Spring)
Hutch, Three Point (4 Spring) add 24” in tandem area - 49’ 8” overall
Open Wheel Wells
36” Beaver Tail
Rear Spring Assisted Loading Ramps 24” x 72” (Requires Beaver Tail)
Rear Hydraulic Ramps 36” x 96” (Requires Beaver Tail) Double Folding (36” x 144”) (Wetline Operations) for Elect./Hyd
Aluminum Wheels (Outside Polished)
275/70R22.5 Tires
Plumbed for Flip Axle and Trailer Brackets
Third Flip Axle

MISCELLANEOUS

Additional Lashing Rings
Special Paint Color