Georgia Office **706-507-3610** **Fax 706-507-3611**
California Office **510-582-4849** **Fax 510-582-9917**

Model LB35-38CS

STANDARD FEATURES	**PLUS 12% FEDERAL EXCISE TAX**
Load Capacity	70,000 lbs. In 16’
Weight	15,900 lbs.
Overall Length	45’
Width	8’6”
Deck Length	30’ (27’ Level Deck + 4’ Dovetail)
Deck Height	38” Loaded
Gooseneck	Flat Deck Wood – w/ 17 Degree Slope – Steel with Traction Bars
Fifth Wheel Height	48”
King Pin Swing Radius	84”
King Pin Setting	18”
Mainframe	16” Wide Flange-Mill Roll “I” Beam
Side Rails	12” Wide Flange-Mill Roll “I” Beam
Cross Members	8” Wide Flange-Mill Roll “I” Beam
Wheel Wells	Covered with Check Plate & Traction Bars
Dovetail	48” Covered with Check Plate & Traction Bars
Loading Ramps	Spring Assist, 24”x 72”
Landing Gear	Two Speed, 50,000 lbs. Capacity
Lashing Rings	8 Per Side (16 total)
Decking	Full 1-3/4” Oak
Suspension	Hutch, 3 Point, Four Spring, with 14,000 lbs. Cap. Springs
Axles	25,000 lbs. Capacity, 77.5” Track, Auto Slack Adjusters, Type 30/30 Brake Chambers, Outboard Drums, ABS
Brakes	16 ½” x 7”
Parking Brakes	Type 30/30 Spring Brakes (2 Axles)
Tires	255/70R22.5 Low Profile Radials
Wheels	8.25x22.5 Steel Disc/ Hub Piloted
Wiring	D.O.T. Sealed Wiring Harness, Sealed Lights Rubber Mounted
Tool Box	Covered in Gooseneck
Mud Flaps	Spray Guard and Anti-Sail
Flag Holders	On All Four Corners
Paint	Yellow/Black (Two Part Primer w/ Two Part Polyurethane Paint)

*****NOTE***** ALL SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE. WEIGHTS AND DIMENSIONS ARE APPROXIMATE

OPTIONAL EQUIPMENT

GOOSENECK

Revolver Greaseless Coupling System (Eliminates Need To Grease 5th Wheel)
Motor Grader Ramps - Wood Filled in Lieu of Check Plate
Flat Top w/ Steel Check Plate In Lieu of Oak
90° Gooseneck With Flat Upper Deck - Wood Filled

MAINFRAME – Fabricated – “I” Beam with Positive Camber

DECK

Additional Length In Deck Area
Additional Width 9’ includes 83.5” Track Axles
10’ includes 95.5” Track Axles
Widening BracketsApitong 1-3/4” (In Lieu of Oak)
Floor Clips (In Lieu of Screws)

BOGIE

No Type 30/30 Spring Brakes
Aluminum Wheels (outside polished)
Single Point 50,000 lb. Cap.
Air Ride 50,000 lb. Cap. (Raises Deck Height 3”)
Dovetail Covered with Wood in Lieu of Check Plate
60” Dovetail Covered with Check Plate & Traction Bars
Rear Hydraulic Ramps (36” x 96”)
Double Folding (36” x 144”) (Wetline Operation

MISCELLANEOUS

Additional Lashing Rings
Special Paint Color