



Georgia Office 706-507-3610
 California Office 510-582-4849

Fax 706-507-3611
 Fax 510-582-9917

Model LB52-33CS

STANDARD FEATURES

PLUS 12% FEDERAL EXCISE TAX

Load Capacity _____	104,000 lbs. In 16'
Weight _____	18,500 lbs.
Overall Length _____	49'
Width _____	8'6"
Deck Length _____	34' (30' Level Deck + 4' Dovetail)
Deck Height _____	33" Loaded
Gooseneck _____	Flat Deck- Wood with 17 Degree Slope – Steel with Traction Bars
Fifth Wheel Height _____	48"
King Pin Swing Radius _____	84"
King Pin Setting _____	18"
Mainframe _____	14" Wide Flange-Mill Roll "I" Beam
Side Rails _____	12" Wide Flange-Mill Roll "I" Beam
Cross Members _____	8" Wide Flange-Mill Roll "I" Beam
Wheel Wells _____	Covered with Check Plate & Traction Bars
Dovetail _____	48" Covered with Check Plate & Traction Bars
Loading Ramps _____	Spring Assist, 24"x 72"
Landing Gear _____	Two Speed, 50,000 lbs. Capacity
Lashing Rings _____	9 Per Side (18 total)
Decking _____	Full 1-3/4" Oak
Suspension _____	Hutch Three Point, Four Spring, with 14,000 lbs. Cap. Spring
Axles _____	25,000 lbs. Capacity, 77.5" Track, Auto Slack Adjusters, Type 30/30 Brake Chambers, Outboard Drums
Brakes _____	12 1/4" x 7 1/2"
Parking Brakes _____	Type 30/30 Spring Brakes (2 Axles)
Tires _____	235/75R17.5 Low Profile Radials
Wheels _____	6.75 x 17.5 Steel Disc
Wiring _____	D.O.T. Sealed Wiring Harness, Sealed Lights Rubber Mounted
Tool Box _____	Covered In Gooseneck
Mud Flaps _____	Spray Guard and Anti-Sail
Flag Holders _____	On All Four Corners
Paint _____	Yellow/Black (Two Part Primer w/ Two Part Polyurethane Paint)

NOTE ALL SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE. WEIGHTS AND DIMENSIONS ARE APPROXIMATE

OPTIONAL EQUIPMENT

GOOSENECK

Revolver Greaseless Coupling System (Eliminates Need To Grease 5th Wheel)
 90° Gooseneck With Flat Upper Deck - Wood Filled
 No Motor Grader Ramps

MAINFRAME – Fabricated – "I" Beam with Postive Camber

DECK

Additional Length In Deck Area
 Additional Width - 9' includes 83.5" Track Axles
 10' includes 95.5" Track Axles
 Widening Brackets
 Apitong 1-3/4" (In Lieu of Oak)
 Floor Clips (In Lieu of Screws)

BOGIE

Type 30/30 Spring Brakes (All Axles)
 Aluminum Wheels (Outside Polished)
 Air Ride 75,000 lb. Cap. (Raises Deck Height 3")
 Dovetail Covered with Wood in Lieu of Check Plate
 60" Dovetail Covered with Check Plate & Traction Bars
 Rear Hydraulic Ramps (36" x 96")
 Double Folding (36" x 144") (Wetline Operations)

MISCELLANEOUS

Additional Lashing Rings
 Special Paint Color