Georgia Office 706-507-3610 **Fax 706-507-3611**
California Office 510-582-4849 **Fax 510-582-9917**

Model LB55-24D

STANDARD FEATURES	**PLUS 12% FEDERAL EXCISE TAX**
Load Capacity	110,000lbs.In 16’
Weight	19,650lbs.
Overall Length	51’ 6”
Deck Length	24’ Cambered Deck
Deck Height	24” Loaded
Gooseneck	Hydraulic Removable, Non-Ground Bearing Design, Two 8” Main Cylinders
Power Source	Set Up For Wet Line
Fifth Wheel Height	48”
King Pin Swing Radius	96”
King Pin Setting	18”
Mainframe	16” Fabricated with Positive Camber (Four I-Beam Design)
Siderails	16” Fabricated with Positive Camber (Four I-Beam Design)
Cross Members	8” I-Beam on 20” Centers
Front Deck Ramps	Tapered Slope with Traction Bars
Boom Trough	“V” Cross Members w/ Steel Grating Center
Wheel Wells	Open
Lashing Rings	8 Per Side (16 total)
Decking	Full 1-3/4” Apitong Covered Outside & Center Open
Widening Brackets	Extends Trailer Width Two Feet In Deck
Suspension	Air Ride with Auto & Manual Controls, 3½” Down + 5” Up
Axles	25,000 lbs. Capacity, 77.5” Track, Auto Slack Adjusters Type 30 Brake Chambers, 16 ½”x 7” Brake Pads, Outboard Drums, 54.5 Axle Spacings
Parking Brakes	Type 30/30 Spring Brakes (2 Axles)
Tires	275/70R22.5 Low Profile Radials
Wheels	8.25x 22.5 Steel Disc Hub Piloted
Tool Box	In Front & Rear of Deck
Wiring	D.O.T. Sealed Wiring Harness, Rubber Mounted LED Lights
Paint	Yellow/Black (Two Part Primer w/ Two Part Polyurethane Paint)

*****NOTE*** ALL SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE. WEIGHTS AND DIMENSIONS ARE APPROXIMATE**

OPTIONAL EQUIPMENT

GOOSENECK

Self Contained 13 H.P. Honda Power Unit-Lockable (With Quick Disconnects)
Revolver Greaseless Coupling System (Eliminates Need To Grease 5th Wheel)
Steel Non-Load Bearing Gooseneck Fenders
Dual King Pin (96” & 110”)

DECK

Additional Length In Deck Area (Max. 2’) Call for Additional Lengths
Center Deck Floored
Paver Special Design-with 8° Load Angle
Front Flip Ramps 18” x 30” (Steel with Traction Bars)
Additional Width 9’ includes 83.5” Track Axles
10’ includes 95.5” Track Axles
Aluminum Center Ramp
18” Loaded Deck Height Design (12” Mainbeams and Siderails)
Drop Side Design - Lowers Side Decks 5”

BOGIE

Type 30/30 Spring Brakes (All Axles)
Air Lift One Axle
Hutch, Four Point (6 spring) add 24” in tandem area -53’ overall
Wheel Well Covers (Welded)
36” Beaver Tail
Rear Spring Assisted Loading Ramps 24” x 72” (Requires Beaver Tail)
Rear Hydraulic Ramps 36” x 96” (Requires Beaver Tail)
Double Folding (36” x 144”) (Wetline Operations)
Aluminum Wheels (Outside Polished)
Plumbed for Flip Axle and Trailer Brackets
Fourth Flip Axle

MISCELLANEOUS

Additional Lashing Rings
Special Paint Color