Georgia Office 706-507-3610 **Fax 706-507-3611**
California Office 510-582-4849 **Fax 510-582-9917**

Model LB35-26

STANDARD FEATURES **Fabricated Mainframe** **PLUS 12% FEDERAL EXCISE TAX**

Load Capacity	70,000 lbs. In 16’
Weight	16,900lbs.
Overall Length	45’
Width	8’6”
Deck Length	20’ Cambered Deck
Deck Height	26” Loaded
Gooseneck	Fixed, Full Width, with Motor Grader Ramps
Fifth Wheel Height	48”
King Pin Swing Radius	84”
King Pin Setting	18”
Mainframe	14” Fabricated with Positive Camber (Four “I”-Beam Design)
Siderails	14” Fabricated with Positive Camber (Four “I”-Beam Design)
Cross Members	8” Wide Flange-Mill Roll “I” Beam
Wheel Wells	Covered with Check Plate & Traction Bars
Dovetail	36”- Covered with Check Plate and Traction Bars
Loading Ramps	Spring Assist, 24”x 72”
Landing Gear	Two Speed, 50,000 lbs. Capacity
Lashing Rings	8 Per Side (16 total)
Decking	Full 1-3/4” Oak
Suspension	Hutch Three Point, Four Spring, with 14,000 lbs. Cap. Spring
Axles	25,000 lbs. Capacity, 77.5” Track, Auto Slack Adjusters, Type 30/30 Brake Chambers, Outboard drums, ABS
Brakes	16 ½” x 7”
Parking Brakes	Type 30/30 Spring Brakes (2 Axles Only)
Tires	255/70R22.5 Low Profile Radials
Wheels	8.25 x 22.5 Steel Disc/Hub Piloted
Wiring	D.O.T. Sealed Wiring Harness, Sealed Lights Rubber Mounted
Tool Box	Covered In Gooseneck
Mud Flaps	Spray Guard and Anti-Sail
Flag Holders	On All Four Corners

Paint _____
_____ Yellow/Black (Two Part Primer w/ Two Part Polyurethane Paint)

*****NOTE***** ALL SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE. WEIGHTS AND DIMENSIONS ARE APPROXIMATE

OPTIONAL EQUIPMENT

GOOSENECK

Revolver Greaseless Coupling System (Eliminates Need To Grease 5th Wheel)
90° Gooseneck With Flat Upper Deck - Wood Filled

DECK

Additional Length In Deck Area
Additional Width 9’ includes 83.5” Track Axles
10’ includes 95.5” Track Axles
Widening Brackets
Apitong 1-3/4” (In Lieu of Oak)
Floor Clips (In Lieu of Screws)

BOGIE

No Type 30/30 Spring Brakes
Aluminum Wheels (Outside Polished)
Air Ride 50,000 lb. Cap. (Raises Height Over Tandem 3”)
Single Point 50,000 lb. Cap.
48” Dovetail Covered with Check Plate & Traction Bars
60” Dovetail Covered with Check Plate & Traction Bars
Rear Hydraulic Ramps (36”x 96”)
Double Folding (36”x 144”) (Wetline Operations)

MISCELLANEOUS

Additional Lashing Rings
Special Paint Color