



Georgia Office 706-507-3610
 California Office 510-582-4849

Fax 706-507-3611
 Fax 510-582-9917

Model LB35-38

STANDARD FEATURES

PLUS 12% FEDERAL EXCISE TAX

Load Capacity	70,000lbs. In 16'
Weight	15,800lbs.
Overall Length	41'
Width	8'6"
Deck Length	29' (26' Level Deck + 3' Dovetail)
Deck Height	38" Loaded
Gooseneck	Exposed Neck w/ Steel Motor Grader Ramps
Fifth Wheel Height	48"
King Pin Swing Radius	84"
King Pin Setting	18"
Mainframe	16" Wide Flange – Mill Roll "I" Beam
Side Rails	12" Wide Flange – Mill Roll "I" Beam
Cross Members	8" Wide Flange – Mill Roll "I" Beam
Wheel Wells	Covered with Check Plate & Traction Bars
Dovetail	36" Covered with Check Plate & Traction Bars
Loading Ramps	Spring Assist, 24"x 72"
Landing Gear	Two Speed, 50,000lbs. Capacity
Lashing Rings	8 Per Side (16 total)
Decking	Full 1-3/4" Oak
Suspension	Hutch Three Point, Four Spring, with 14,000 lbs. Cap. Springs
Axles	25,000lbs. Capacity, 77.5" Track, Auto Slack Adjusters, Type 30/30 Brake Chambers, outboard drums, ABS
Brakes	16 1/2" x 7"
Parking Brakes	Type 30/30 Spring Brakes (2 Axles Only)
Tires	255/70R22.5 Low Profile Radials
Wheels	8.25x22.5 Steel Disc/ Hub Piloted
Wiring	D.O.T. Sealed Wiring Harness, Sealed Lights Rubber Mounted
Tool Box	Covered In Gooseneck
Mud Flaps	Spray Guard and Anti-Sail
Flag Holders	On All Four Corners
Paint	Yellow/Black (Two Part Primer w/ Two Part Polyurethane Paint)

NOTE ALL SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE. WEIGHTS AND DIMENSIONS ARE APPROXIMATE

OPTIONAL EQUIPMENT

GOOSENECK

Revolver Greaseless Coupling System (Eliminates Need To Grease 5th Wheel)
 No Motor Grader Ramp
 90° Gooseneck With Flat Upper Deck - Wood Filled

MAINFRAME – Fabricated "I" Beam with Positive Camber

DECK

Additional Length In Deck Area
 Additional Width 9' includes 83.5" Track Axles
 10' includes 95.5" Track Axles
 Widening Brackets
 Apitong 1- 3/4" (In Lieu of Oak)
 Floor Clips (In Lieu of Screws)

BOGIE

No Type 30/30 Spring Brakes
 Aluminum Wheels (Outside Polished)
 Single Point 50,000 lb. Cap.
 Air Ride 50,000 lb. Cap. (Raises Deck Height 3")
 Dovetail Covered with Wood in Lieu of Check Plate
 48" Dovetail Covered with Check Plate & Traction Bars
 60" Dovetail Covered with Check Plate & Traction Bars
 Rear Hydraulic Ramps (36" x 96")
 Double Folding (36" x 144") (Wetline Operation)

MISCELLANEOUS

Additional Lashing Rings
 Special Paint Color