



Georgia Office 706-507-3610
 California Office 510-582-4849

Fax 706-507-3611
 Fax 510-582-9917

Model LB35-33CS

STANDARD FEATURES	PLUS 12% FEDERAL EXCISE TAX
--------------------------	------------------------------------

Load Capacity _____	70,000 lbs. In 16'
Weight _____	15,900 lbs.
Overall Length _____	45'
Width _____	8'6"
Deck Length _____	30' (26' Level Deck + 4' Dovetail)
Deck Height _____	33" Loaded
Gooseneck _____	Flat Deck Wood w/17 Degree Slope – Steel with Traction Bars
Fifth Wheel Height _____	48"
King Pin Swing Radius _____	84"
King Pin Setting _____	18"
Mainframe _____	14" Wide Flange-Mill Roll "I" Beam
Side Rails _____	12" Wide Flange-Mill Roll "I" Beam
Cross Members _____	8" Wide Flange-Mill Roll "I" Beam
Wheel Wells _____	Covered with Check Plate & Traction Bars
Dovetail _____	48" Covered with Check Plate & Traction Bars
Loading Ramps _____	Spring Assist, 24"x 72"
Landing Gear _____	Two Speed, 50,000 lbs. Capacity
Lashing Rings _____	8 Per Side (16 total)
Decking _____	Full 1-3/4" Oak
Suspension _____	Hutch 3 Point, Four Spring w/ 14,000 lbs Cap Springs
Axles _____	25,000lbs cap 77.5" Track, Auto Slack Adjust, Type 30/30 Brake Chambers, Outboard Drums, ABS
Brakes _____	12 1/4" x 7 1/2"
Parking Brakes _____	Type 30/30 Spring Brakes
Tires _____	235/75R17.5 Low Profile Radials
Wheels _____	6.75 x 17.5 Steel Disc
Wiring _____	DOT Sealed Wiring Harness Sealed Lights Rubber Mounted
Tool Box _____	Covered in Gooseneck
Mud Flaps _____	Spray Guard and Anti-Sail
Flag Holders _____	On All Four Corners
Paint _____	Yellow/Black (Two Part Primer w/ Two Part Polyurethane Paint)

NOTE ALL SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE. WEIGHTS AND DIMENSIONS ARE APPROXIMATE

OPTIONAL EQUIPMENT

GOOSENECK

- Revolver Greaseless Coupling System (Eliminates Need To Grease 5th Wheel)
- Motor Grader Ramps - Wood Filled in lieu of Check Plate
- Flat Top w/ Steel Check Plate 90 degree Gooseneck With Flat Upper Deck - Wood Filled

MAINFRAME – Fabricated – "I" Beam with Positive Camber

DECK

- Additional Length in Deck Area _____
- Additional Width 9' includes 83.5" Track Axle
- 10' includes 95.5" Track Axle
- Widening Brackets
- Apitong (In Lieu of Oak)
- Floor Clips (In Lieu of Screws)

BOGIE

- No Type 30/30 Spring Brakes
- Aluminum Wheels (Outside Polished)
- Single Point 50,000 lb. Cap.
- Air Ride 50,000 lb. Cap. (Raises Deck Height 3")
- Dovetail Covered with Wood in Lieu of Check Plate
- 60" Dovetail Covered with Check Plate & Traction Bars
- Rear Hydraulic Ramps (36" x 96")
- Double Folding (36" x 144") (Wetline Operation)

MISCELLANEOUS

- Additional Lashing Rings
- Special Paint Color